

Winter Parking Lot and Sidewalk Maintenance

Key Information Needed:

- Pavement Temperature (it will be different than air temperature)
- Parking lot area (or drive lane distance) = Length x Width
- Amount of material your truck or sander delivers at each setting and speed.

TIPS:

- De-icers melt snow and ice. They provide no traction on top of snow and ice.
- Anti-icing prevents the bond from forming between pavement and ice.
- De-icing works best if you plow before applying material.
- Pick the right material for the pavement temperatures.
- Sand only works on top of snow as traction. It provides no melting.
- Anti-icing chemicals must be applied prior to snow fall.
- NaCl (road salt) does not work on cold days, less than 15° F.


Use less! About one tsp. of salt contaminates 5 gallons of water.



Melt Times for Salt (NaCl) at Different Pavement Temperatures

Pavement Temp. °F	One Pound of Salt (NaCl) melts	Melt Times
30°	46.3 lbs of ice	5 min.
25°	14.4 lbs of ice	10 min.
20°	8.6 lbs of ice	20 min.
15°	6.3 lbs of ice	1 hour
10°	4.9 lbs of ice	Dry salt is ineffective and will blow away before it melts anything

Pick your material based on lowest practical melting temperature, not eutectic temperature which is often listed on the bag.



Melting Characteristics

Chemical	Lowest Practical Melting Temp.
CaCl ₂ (Calcium Chloride)	-20° F
KAc (Potassium Acetate)	-15° F
MgCl ₂ (Magnesium Chloride)	-10° F
NaCl (Sodium Chloride)	15° F
CMA (Calcium Magnesium Acetate)	20° F
Blends	Check with manufacturer
Winter Sand/Abrasives	Never melts—provides traction only



Variables affecting application rate



Increase rate if:

Compaction occurs & cannot be removed mechanically
There is a lot of snow left behind

Decrease Rate if:

Light snow or light freezing rain
Pavement temperature is rising
Subsequent applications

Help protect our lakes, streams, wetlands, and drinking water!

Use best practices for winter maintenance.



UNIVERSITY OF MINNESOTA



Deicing Application Rate Guidelines for Parking Lots and Sidewalks

These rates are adapted from road application guidelines (Mn Snow & Ice Control Field Handbook, Manual 2005-1). Develop your own application rates using the guidelines as a starting point and modify them incrementally over time to fit your needs. The area should first be cleared of snow prior to applying chemical.

Pavement Temp. (°F) and Trend (↑↓)	Weather Condition	Maintenance Actions	Application Rate in lbs. per 1000 square foot area			
			Salt Prewetted/ Pretreated With Salt Brine	Salt Prewetted/ Pretreated With Other Blends	Dry Salt	Winter Sand (abrasives)
>30°↑	Snow	Plow, treat intersections only	0.75	0.5	0.75	not recommended
	Frz. Rain	Apply chemical	1.25	1.0	1.5	not recommended
30°↓	Snow	Plow & apply chemical	1.25	1.0	1.5	not recommended
	Frz. Rain	Apply chemical	1.5	1.25	1.75	not recommended
25 - 30°↑	Snow	Plow & apply chemical	1.25	1.0	1.5	not recommended
	Frz. Rain	Apply chemical	1.5	1.25	1.75	not recommended
25 - 30°↓	Snow	Plow & apply chemical	1.25	1.0	1.5	not recommended
	Frz. Rain	Apply chemical	1.75	1.5	2.25	3.25
20 - 25°↑	Snow or Frz. Rain	Plow & apply chemical	1.75	1.5	2.25	3.25 for frz. rain
20 - 25°↓	Snow	Plow & apply chemical	2.0	2.0	2.75	not recommended
	Frz. Rain	Apply chemical	2.5	2.0	3.0	3.25
15° to 20°↑	Snow	Plow & apply chemical	2.0	2.0	2.75	not recommended
	Frz. Rain	Apply chemical	2.5	2.0	3.0	3.2
15° to 20°↓	Snow or Frz. Rain	Plow & apply chemical	2.5	2.0	3.0	3.25 for frz. rain
0 to 15°↑ ↓	Snow	Plow, treat with blends, sand hazardous areas	not recommended	3.0	not recommended	5.0 spot treat as needed
< 0°	Snow	Plow, treat with blends, sand hazardous areas	not recommended	4.5	not recommended	5.0 spot treat as needed

To determine the amount of material needed, take the application rate x parking lot area / 1000 ft². **Example:** Given a 300,000 sq. ft. parking lot and an application rate of 1.5 lbs/1000ft² 1.5 x 300,000 = 450,000 450,000/1000 = 450 lbs (nine 50 lb. bags).

Anti-Icing Guidelines			
These are a starting point only. Adjust based on your experience.			
Condition	Gallons/1000 sq. ft.		Other Products
	MgCl ₂	Salt Brine	
1. Regularly scheduled applications	0.1 - 0.2	0.25 - 0.3	Follow manufacturers' recommendations
2. Prior to frost or black ice event	0.1 - 0.2	0.25 - 0.3	
3. Prior to light or moderate snow	0.1 - 0.2	0.2 - 0.4	

CAUTION: Too high an application rate may result in slippery conditions or tracking.